



LUXURY EYE

MATERIAL SAFETY DATA SHEET

BLACK LASH ADHESIVE – SPARKLE

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION.

COMPANY NAME: LUXURY EYE LTD.

ADDRESS: 4 Langdale Court, Market Square, Witney, OX28 6FG, United Kingdom.

PHONE: 01993 702972.

2. COMPOSITION / INFORMATION ON INGREDIENTS.

No.	INCI NAME	CAS No.	% BY WEIGHT
1	ETHYL 2-CYANOACRYLATE	7085-85-0	< 90%
2	PMMA	9011-14-7	< 10%

3. HAZARDOUS IDENTIFICATION.

- Emergency overview: Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.

- Potential health effects: May cause sensitization by inhalation. Narcotic effects, headache, dizziness, vomiting. Skin: dryness. Eye: irritation.

- Potential environmental effects: Not available.

- Signs and symptoms of exposure: Vapor is irritating to eyes and mucous membranes above TLV. Prolonged and repeated overexposure to vapours may produce symptoms of non-allergic asthma in sensitive individuals.

- Existing conditions aggravated by exposure: Unknown.

- Potential chemical and physical effect: Polymerized by water, alcohol, amines, and alkaline substance. Produce heat when polymerized.

4. FIRST AID MEASURES.

- Inhalation: Evacuate from further exposure. If unconsciousness occurs, seek immediate medical assistance and call a physician.
- Eye contact: Flush thoroughly with fresh water for at least 15 min.
- Skin contact: Remove contaminated clothing. Wash contact areas with soap and much water.
- Ingestion: Get medical attention immediately.

Get medical attention if symptoms persist.

5. FIRE FIGHTING MEASURES.

- Extinguishing Media: Use Carbon dioxide, foam, dry chemical.
- Special Fire-fighting procedures: To prevent a possible health hazard, wear a self-contained breathing apparatus.
- Hazardous products formed by fire or thermal decomposition: Irritating organic fragments.
- Unusual fire and Explosion hazards: None.

6. ACCIDENTAL RELEASE MEASURES.

- Small Spills: Absorb spill with inert material (dry cloth, dry sand), then place in a chemical waste container using non-sparking tools. Flush residual spill (area) with plenty of water.
- Large Spills: Dike for later disposal. Wash with plenty of water. Evacuate non-essential personnel. Shut off all sources of ignition: No fires, smoking or flames in area. Ventilate area after material pick up is completed.

7. HANDLING AND STORAGE.

- Handling Precautions: Keep away from sources of ignition and heat. No smoking or flames in working area. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Wear proper protective equipment. Use only in well ventilated areas. Use exhaust ventilation to keep air concentration below exposure limit. Keep container tightly closed when not in use. Install emergency showers and eye wash facility in working area.
- Storage Requirements: Keep away from all possible source of ignition. Store in a cool, dry, well ventilated location. Keep container tightly closed. Keep away from combustible materials, heat, steam pipe or sunlight. Keep away from oxidizing materials.
- Other Precautions: Wash hands, face and gargle after work. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, or using the rest room. Keep out of reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION.

Protective Clothing/Equipment:

- Protective gloves: Polyethylene gloves. No rubber.
- Eye protection: Safety glasses, face shield.
- Skin protection: Other protective clothing or equipment impervious clothing, apron, and boots. Barrier creams, etc.

9. PHYSICAL AND CHEMICAL PROPERTIES.

- Appearance: Transparent or lightly yellowish liquid.
- Odour: Non smell.
- Odour threshold: N/A - pH: 4~6.
- Melting Point/Freezing Point: <-20 °C.
- Initial boiling Point and boiling range: Above 190 °C - Flash point: 95 °C (open cup).
- Evaporation rate: N/A.
- Flammability (solid, gas): Liquid.
- Upper/lower flammability or explosive limits: N/A.
- Vapor pressure: <1 pa (25 °C).
- Relative density: 0.9~1.1 (water=1).
- Solubility(ies): Not soluble in water. Slightly soluble in alcohol, acetone, MEK, toluene, DMF, nitromethane.
- Partition coefficient: n-octanol/ water: N/A.
- Autoignition temperature: 330 °C.
- Decomposition temperature: N/A.

10. STABILITY AND REACTIVITY.

- Condition to avoid: High humidity, high temperature or direct sunlight.
- Stability: Stable (cool and dry area.).
- Materials to avoid: Polymerized by contact with water, alcohols, amines, alkalis.

- Hazardous decomposition or by-products: CO₂, oxides and nitrogen and unknown hydrocarbons.

11. TOXICOLOGICAL INFORMATION.

No information available.

12. ECOLOGICAL INFORMATION.

No information available.

13. DISPOSAL CONSIDERATION.

Dispose of unused product or contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state, and local regulatory agencies to ascertain proper disposal procedures.

14. TRANSPORT CONSIDERATION.

- Air: IATA Regulation.
- Proper shipping name: Unrestricted.
- Class or division: Unrestricted.
- UN or ID number: None.
- Road: Should follow the packaging standard.
- Sea: Should follow the packaging standard.

15. REGULATORY INFORMATION.

No information available.

16. OTHER INFORMATION.

Drawing up date: 2018.03.08.

NOTE: This information is furnished without warranty, express or implied, except that it is accurate the best knowledge of Luxury Eye Ltd. It relates only to the specific material designated herein and does not relate to use in combination with any other material or process. Luxury Eye Ltd assume no responsibility for use or reliance upon this information